

PINZE PORTAELETTRODI ELECTRODE HOLDERS



PARVA 2

EN 60974-11

Corpo in ottone pressofuso e rivestimenti isolanti in materiali termoindurenti, ininfiammabili e anticalore. Serraggio cavo mediante grani a cava esagonale. Molla a compressione isolata. Leva in ottone forgiato e isolato.

Die-cast brass body and insulating coatings in thermosetting materials, flame resistant and heat-proof. Cable clamping by recessed hex-head dowels. Insulated compression spring. Insulated forged brass lever made in thermosetting material.



COD.	A	A	Ø	⊗	↓	↔	CLASS	⊠
	60%	35%	mm	mm ²	gr	mm		n°
PIN 000 006	150	200	2-3,2	16-25	325	210	B	25



ALFA 1

EN 60974-11

Specifica per l'utilizzo con generatori di corrente a medio e basso amperaggio. Corpo in alluminio pressofuso ed isolamento in materiale termoindurente.

Specific for use with medium and low amperage generators.

Die-cast aluminum body and insulation in thermosetting material.



COD.	A	Ø	⊗	↓	↔	CLASS	⊠
	60%	mm	mm ²	gr	mm		n°
PIN 000 143	160	1,6-4	25	115	197	B	100

