



Datos Técnicos			TR 1	TR 2	TR 4	WF 2	WF 4	DTR4 A/V
Single phase input 50/60Hz	V		48	48	48	48	48	48
Motor	W		50	100	100	100	100	100
Rodillos	No.		2	2	4	2	4	4
Velocidad	m/min		0.5-24	0.5-24	0.5-24	0.5-24	0.5-20	0.5-24
Hilo Macizo (Acero)	Ø mm		0.6 - 1.6	0.6 - 2.4	0.6 - 2.4	0.6 - 2.4	0.6 - 2.4	0.6 - 2.4
Factor de marcha	A	60 %	600	600	600	600	600	600
		100 %	460	460	460	460	460	460
Dimensiones	mm	d	450	450	450	570	570	450
		w	230	230	230	275	275	230
		h	315	315	315	400	400	315
Peso	Kg		10.5	11.5	11.5	16	17	11.5

Datos Técnicos			DF 4	ES 5	TA 4	HS 4	HT 4
Single phase input 50/60Hz	V		48	48	48	48	48
Motor	W		100	100	100	100	100
Rodillos	No.		4	4	4	4	4
Velocidad	m/min		0.5-20	0.5-20	0.5-20	0.5-22	0.5-22
Hilo Macizo (Acero)	Ø mm		0.6 - 2.4	0.6 - 2.4	0.8 - 2.4	0.6 - 2.4	0.6 - 2.4
Factor de marcha	A	60 %	600	600	600	600	600
		100 %	460	460	460	460	460
Dimensiones	mm	d	570	570	570	650	650
		w	275	275	275	290	290
		h	400	400	400	520	520
Peso	Kg		17	17	17	17	